

جداول عیب یابی دستگاههای اسپلیت مدل دیواری

ASG...

جدول تشخیص عیب اسپلیتهای دیواری مدل ASG اجنرال

نوع عیب (Error Contents)	نمایش نوع عیب روی پنل داخلی		
	Operation چراغ قرمز	Timer چراغ زرد	Swing چراغ نارنجی
برد یونیت داخلی ایراد دارد	چشمک زن سریع	چشمک زن سریع	خاموش
سنسور دمای هوای برگشت یونیت داخلی ایراد دارد.	دوبار آهسته چشمک می زند	چشمک زن سریع	خاموش
سنسور دمای هوای برگشت یونیت داخلی اتصالی دارد .	دوبار آهسته چشمک می زند	چشمک زن سریع	چشمک زن سریع
سنسور خط لوله یونیت داخلی ایراد دارد.	سه بار آهسته چشمک می زند	چشمک زن سریع	خاموش
سنسور خط لوله یونیت داخلی اتصالی دارد .	سه بار آهسته چشمک می زند	چشمک زن سریع	چشمک زن سریع
فن یونیت داخلی ایراد دارد .	شش بار آهسته چشمک می زند	چشمک زن سریع	خاموش

ERROR CONTENTS

○ : Fast flashing

● : Slow flashing

Error contents	Error display		
	OPERATION (Red)	TIMER (Green)	SWING (Orange)
Indoor unit circuit board error	○	○	Off
Indoor unit room temperature sensor wire opened	2 times ●	○	Off
Indoor unit room temperature sensor wire short circuited	2 times ●	○	○
Indoor unit piping sensor wire opened	3 times ●	○	Off
Indoor unit piping sensor wire short circuited	3 times ●	○	○
Indoor unit fan error	6 times ●	○	Off

ERROR DETECTION

Display		Error
Operation LED	Timer LED	
Off	8 flash	Wired remote control error (Communication error)
2 flash	2 flash	Indoor temperature thermistor open / short
	3 flash	Indoor unit, heat exchanger middle thermistor open / short
4 flash	2 flash	Forced automatic SW welded (Indoor unit control error)
6 flash	2 flash	Indoor fan motor, Abnormal lock
	3 flash	Indoor fan motor, Abnormal rotation
0.1 sec on/off	0.1 sec on/off	Model information error

ASGA09,12RUC
ASGS09,12RVC
ASGC12AWT
ASGS12AUC

ERROR DETECTION

Large division indication

LED indication		Error contents
Operation lamp (Red)	Timer lamp (Green)	
● (2 times)	○	thermistor error
● (4 times)	○	control unit error (indoor unit)
● (6 times)	○	fan motor error (indoor unit)

Small division indication

LED indication		Error contents
Operation lamp (Red)	Timer lamp (Green)	
○	● (2 times)	thermistor error (room temp.)
○	● (3 times)	thermistor error (heat exchanger)
○	● (2 times)	MANUAL AUTO button error
○	● (4 times)	power source Hz decision error
○	● (2 times)	lock error
○	● (3 times)	rpm error

● : 0.5s on/off repeated

○ : 0.1s on/off repeated

E R R O R D I S P L A Y

hamzeh.askari@gmail.com

Troubleshooting check table

Operation lamp : Red lamp
Timer lamp : Green lamp

Large division indication			Small division indication		
Error contents	LED indication		Error contents	LED indication	
thermistor error	RED lamp	● (2 times)	thermistor error (room temp.)	RED lamp	○
	Green lamp	○	thermistor error (heat exchanger)	Green lamp	● (2 times)
control unit error (indoor unit)	RED lamp	● (4 times)	MANUAL AUTO button error	RED lamp	○
	Green lamp	○	power source Hz decision error	Green lamp	● (2 times)
fan motor error (indoor unit)	RED lamp	● (6 times)	lock error	RED lamp	○
	Green lamp	○	rpm error	Green lamp	● (2 times)
				RED lamp	○
				Green lamp	● (3 times)

● : 0.5s ON/OFF repeated

○ : 0.1s ON/OFF repeated